

HB

299

COMMITTEE REPORT

HOUSE

FURTHER: FINANCE

February 26, 1978

Date: _____

Mr. Speaker:

The Committee on STATE AFFAIRS has had HB 299

an act making a special appropriation to the Department of Community and Regional Affairs for a study of the effects of landslides and landslides on Bodie Island, of date

under consideration and (a majority of the committee) (the committee) reports it back with the following recommendations:

- do pass do not pass
- do pass with attached amendments(s)
- replace with CS for _____ same title
 new title
- and recommends _____
- AND attaches a "Letter of Intent" New Fiscal Note
- reports it back without recommendation
- referred to the _____ Committee

MEMBERS SIGNING
DO PASS

MEMBERS HAVING
OTHER RECOMMENDATIONS:

CHAIRMAN

Funding Information
General Fund \$900,000
Other Funds -0-
\$900,000

Introduced: 2/26/79
Referred: State Affairs and
Finance

State Affairs
BY THAROFF

1 IN THE HOUSE

2 CS for HOUSE BILL NO. 299

3 IN THE LEGISLATURE OF THE STATE OF ALASKA
4 ELEVENTH LEGISLATURE - FIRST SESSION

5 A BILL

6 For an Act entitled: "An Act making a special appropriation to the Depart-
7 ment of Natural Resources for a study of
8 the effects of landslides and tsunamis on Kodiak
9 Island; and providing for an effective date."

10 BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF ALASKA:

11 * Section 1. The sum of ^{\$ 479,000} ~~500,000~~ is appropriated from the general fund to
12 the Department of Natural Resources ~~Community and Regional Affairs~~ for geotechnic studies of
13 the Pillar Mountain landslide and tsunamic hazard area on Kodiak Island, and
14 ~~for preliminary slope stabilization design.~~

15 * Sec. 2. The unexpended and unobligated portion of this appropriation
16 lapses into the general fund June 30, 1980.

17 * Sec. 3. This Act takes effect ~~July 1, 1979~~ immediately

immediately

21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

Div of Geological
Geophysical Services



DEPARTMENT OF THE ARMY
WATERWAYS EXPERIMENT STATION, CORPS OF ENGINEERS
P. O. BOX 631
VICKSBURG, MISSISSIPPI 39180

IN REPLY REFER TO WESSR

21 April 1978

Dr. Reuben Kachadoorian
U. S. Geological Survey
345 Middle Field Road
Menlo Park, CA 94025

Dear Reuben:

As requested after the Kodiak meeting, a revised outline of an investigation to obtain needed data and possible costs for evaluating the Pillar Mountain slide is inclosed (Incl 1). Inclosure 1 could be used to answer Mr. Stewart Denslow's request to you for more details. As revised, the possible costs and time for each of the five phases are listed below.

- a. Phase I. Site investigation to obtain needed data on current movements, surface and subsurface geology, and engineering properties of in situ material and defects (4 months plus 4-6 months of slope indicator readings). \$447,300
 - b. Phase II. Analyses to develop type of slide mechanism, slide geometry, current stability, and probability of rapid slide movement (5 months). 100,000
 - c. Phase III. Time displacement and velocity predictions if Phase II shows high probability of rapid slide movement (3 months). 45,000
 - d. Phase IV. Wave height predictions from numerical hydraulic model, if warranted by Phase III (4 months). 27,000
 - e. Phase V. Wave height and run-up predictions from hydraulic physical model, if warranted by Phases III and IV (12 months). 227,000
- Total \$846,300
- Plus 10% contingency 84,630
- Total possible cost \$930,930

WESSR

21 April 1978

Dr. Reuben Kachadoorian

I contacted Mr. Ron Backer, Spokane Mining Research Center, on precise air photo monitoring of landslide movements. He sent the report "Rapid Monitoring of Coal Refuse Embankments" (Incl 2). Ron referred me to Mr. Larry Roth of CH2M Hill for costs. Mr. Roth's guess on costs was \$600-\$1000 for one flight, including data reduction to provide X, Y, Z coordinates. He is checking further to obtain a better cost estimate for Kodiak.

As you know, we cannot begin any work, if requested, until October 1978. Parts of Phase I might be handled by the State or Kodiak Burrough initially to get the field work underway this season. Another possibility is the Advanced Technology Group at Dames and Moore. Dr. Peter Cundall and others in this group have the capability for the work, including velocity predictions possibly using Dr. Cundall's computer model for jointed rock masses. The capability for numerical and physical hydraulic model studies is unique with the Waterways Experiment Station.

If you need further assistance, please call me at area code 601; 636-3111, extension 2604.

Sincerely yours,

Bill

2 Incl
As stated

W. E. STROHM, JR.
Res Civil Engineer
Engineering Geology and
Rock Mechanics Division

- April 21, 1978

Summary of Required Data and Approximate Costs for
Evaluation of Pillar Mountain Slide Area, Kodiak, Alaska

Phase I: Site investigation to obtain needed data to evaluate current movement, existing stability, and potential for rapid landslide.

A. Surface movement observation program.

1. Monthly survey (horizontal and vertical) of line of spikes along Abbott Highway from old docks to new docks. Nine surveys @ \$2,000 each 6,000
~~12,000~~

\$ 18,000

2. Bimonthly precise airphoto surveys of markers inside and outside the slide area (including DH-1, DH-2, C-1, C-2, and S-1) to further define surface movement directions. Four surveys @ \$5,000 each (CH2M engineers) 20,000

3. Supplement to 2 above. Electronic Distance Measurement (EDM) survey of targets inside slide area from two locations on Gull Island (0.6 miles away). Eight monthly surveys @ \$2,000 each 16,000 12,000

16,000

B. Collect and review existing reports and information, including movements of new city dock and determine if White Alice Station structures have experienced movement or distress. One engineer, three weeks @ \$1200/week

3,600 ~~3,600~~

C. Field reconnaissance.

1. Inspect old land slide areas along Inner Harbor to determine possible location of slide debris (i.e., at base of slide or cut in the harbor)

2. Inspect Gull and Uski Islands to check for ancient slide debris or how islands were formed

IC Two geologists, three weeks each @ \$1200/week plus travel (\$2,000) 9,200

9,200

D. Geological mapping to refine surface geology, crack pattern, joint sets, bedding, etc (includes low-level air photography, field mapping, and office work) 45,000 45,000

45,000

Subtotal IA-ID (\$111,800)

(\$111,800)

Sheet 1

E. Subsurface Investigations.

1. Four core borings to obtain 4-in.-diam cores of beds and joints (may require slant holes)	
a. Near DH-2 to depth of Inner Harbor, elevation 145 to elevation 72, 210 ft @ \$100/ft	\$ 21,000
b. Near center of main slide along Abbott Highway, elevation 50 to elevation 72, 122 ft	12,200
c. Vicinity of DH-1, elevation 900 to elevation 100, 800 ft	80,000
d. Vicinity of S-1, elevation 1100 to elevation 700, 400 ft	40,000
e. Shipment of samples	10,000
2. Borehole camera survey of four core borings @ \$4,000 each	16,000
3. Grout slope indicator casing in four borings and install "poor boy" in each (3-ft piece of pipe in bottom of hole attached to airplane cable), 1,532 ft @ \$25/ft	38,300
4. Install piezometers at three depths in two additional borings, one near DH-1 and one near the core boring along Abbott Highway, 900 ft @ \$40/ft	36,000
5. Field supervision and logging of core borings. Two geologists, 20 weeks each @ \$1,200/week plus travel	<u>52,000</u>
IE Subtotal	(\$305,500)

F. Laboratory tests.

1. Drained direct shear tests on selected core samples of slide debris base material, weak fracture zones, weaker strata of argillites and graywacke material, 20 tests @ \$1,000/test	\$ 20,000
--	-----------

2. Repeated direct shear tests on existing joints, joint filling, or precut sections of core samples to determine residual shear strengths, 10 tests @ \$1,000/test	<u>10,000</u>
IF Subtotal	(\$ 30,000)
Phase I Subtotal	\$447,300

Phase II: Analyses to evaluate potential for rapid slide.

A. Analysis and interpretation of data, define slide mechanism and geometry, determine existing stability, and assess probability of rapid slide movement. Four-man engineer and geologist team, 16 weeks @ \$1,200/week	\$ 76,800
B. Computer time, drafting, photo reduction, and report	<u>23,200</u>
Phase II Subtotal	\$100,000

Phase III: Velocity predictions.

A. Revision of mathematical model program.	\$ 10,000
B. Analyses, two engineers, 10 weeks each @ \$1,200/week	25,000
C. Computer time, drafting, photo reduction, and report	<u>10,000</u>
Phase III Subtotal	\$ 45,000

Phase IV: Wave prediction, numerical model.

It is believed that the WES numerical model should be used initially to define the severity of the wave problem. It can provide an estimate of the initial wave height within a 25 percent accuracy and the time of the wave's arrival from the source within 10 percent accuracy at any selected location within the area of consideration. Information needed to conduct the numerical model includes:

- A. Bathymetry of the area of consideration.
- B. Landslide alignment or direction of slide if it is anticipated that the slide will not move along the landslide axis (from Phase II).

- C. An assumed cross section of the landslide as it enters and travels through the water (from Phase II).
- D. The velocity and final position of the slide material or better, a calculated or hypothesized time versus displacement curve of the slide (from Phase III).

Assuming a maximum of 10 test cases are required to define the problem, time and cost estimates are as follows:

Item	Time (weeks)	Cost
Revitalizing and adapting present model to Kodiak scheme	4	\$ 5,000
Set up and conduct 10 test cases	4	13,000
Letter report	2	1,000
Final report	8	8,000
Total	18	\$ 27,000

Since the Rock Mechanics Division's Landslide Velocity Numerical Model Program and the Wave Dynamics Division's Numerical Wave Prediction Model Program both operate on a time-step basis, it would be advantageous to combine the operation of the two programs once a specific landslide scheme is selected. Should this be desired, it is estimated that reprogramming contributions by the Wave Dynamics Division would not exceed an additional cost of about \$5,000 and four weeks' time.

Phase V: Hydraulic physical model.

If the numerical study wave-height predictions are not of sufficient accuracy and/or the wave heights need refining, or if further detailed information such as wave run-up, extent of area inundated, and techniques to reduce the severity of the wave action are required, a physical model should be considered. Although such a model is expensive, its application is much more versatile. It is recommended that the model include the area shown on Fig. 1 and that the model scale not be greater than 1:100. Model scales greater than 1:100 would increase the viscosity effect of the model and reduce the accuracy of wave height and run-up measurements. Reproducing the proposed prototype area at a 1:100 undistorted scale would require about 7612 sq ft of model area. This is considerably more area than was estimated in the initial estimate (November 1976). Also, the size and layout of the landslide mass described in Kachadoorian and

Slater's report indicates that the existing model landslide mechanism is not wide enough or structurally strong enough to accommodate the proposed Kodiak landslide; thus our mechanism will have to be reconstructed to meet the wider and heavier loads. Based on these assumptions, time and cost estimates for the physical model are as follows:

Item	Time (weeks)	Cost
Design and Construction (including all model construction, rehabilitation and preparation of landslide material)	16	\$141,000
Model testing	16	60,000
Data analysis, conferences, travel, etc.	4	10,000
Report:		
Draft	4	5,000
Final	<u>12</u>	<u>11,000</u>
Total	52	\$227,000

Information needed to construct and operate the physical model is as follows:

- A. Topography data of the land areas included in the model layout, especially land-water interfacing (slope, vertical walls, etc.), along the immediate shoreline from Gibson Cove through Kodiak Harbor.
- B. Bathymetry of the water bodies enclosed by the model (if better survey data are not available, existing C&GS charts can be used to reproduce the required areas of St. Paul's Harbor and the Inner Anchorage area; however, additional contours are needed along the coastal shoreline from Gibson Cove through Kodiak Harbor).
- C. In-place mass-volume-elevation-shape characteristics of the various probable landslides (from Phase II).
- D. Assumptions as to what size pieces the landslide mass will break into upon sliding (from Phase II).